


GRLAIQSM M56



Stryp/backventil M 5-6mm

Betyg: Inte betygsatt ännu

Pris

Pris 154,68 kr

Pris utan moms 123,74 kr

Rabatt

Momsbelopp 30,94 kr

[Ställ en fråga om denna produkt](#)

Produktdatasheet

|         |                                         |
|---------|-----------------------------------------|
| Version | exhaust air flow controlling (Standard) |
| Ø       | M 5                                     |
| D [mm]  | 6                                       |
| H [mm]  | 26,5                                    |
| L [mm]  | 16,4                                    |
| Note    | RoHS-compliant                          |
| Weight  | 9,1 g / pc.                             |

Customs duty number: 84812090

Beskrivning

Arbetsstryck:

0-10 bar

Temperaturvariation:

0 ° C till max. + 60 ° C

Funktionsprincip :

Begränsar flödet i en riktning, medan flödet fortfarande obegränsat i den andra riktningen. Standard konstruktion av stryp/backventilen är "frånluftsfloresreglerande". Om de är inskrivade i en cylinder, till exempel, då ger de ett jämnt flöde och stadigt flöde. I fallet med cylinder med små volymer (en liten diameter / låg slagfrekvens ), använd istället specialutförande "tilluftsfloresreglerande" -konstruktion.

All rights reserved for the manufacturer. No part of this document may be reproduced without written permission. The manufacturer is not responsible for any damage caused by the use of this product. The manufacturer is not responsible for any damage caused by the use of this product. The manufacturer is not responsible for any damage caused by the use of this product.