# GAI 12 LR MSV

Rak skärringskoppling. 12 L-G 3/8", nickelplätterad mässing

Betyg: Inte betygsatt ännu
**Pris**
Pris 120,46 kr

Pris utan moms 96,37 kr

Rabatt

Momsbelopp 24,09 kr

Ställ en fråga om denna produkt

Beskrivning

**Technical data**

Model series light model series

Tube Ø outer [mm] 12 L

Female thread G 3/8"

Operating pressure with hard copper tube [bar] 75

Temperature range [°C] -60 to +300

Further information on GAI12LRMSV

Weight 55 g / Pcs

GTIN 4050571480264

Customs duty number 74122000

RoHS compliant Yes

Description - Screw cutting ring fitt. 12 L-G 3/8", nickel-plated brass

Materials:

Body: nickel-plated brass, cutting ring: brass

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.