

SV 14 8-0,27 MS



TÜV-säkerhetsventil G 1/4 "(DN8), 0,27 bar, Mässing

Betyg: Inte betygsatt ännu

Pris

Pris 496,38 kr

Pris utan moms 397,10 kr

Rabatt

Momsbelopp 99,28 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Properties

Material Brass

Thread G 1/4"

reaction pressure [bar] 0.27

Blow-off capacity* [m³/h] 13.5

H [mm] 55

h [mm] 10

SW [mm] 17

Item description

Materials:

Body: brass, 1.4571 or 1.4401, seal: FKM

Temperature range:

TÜV säkerhetsventil-fast, DN 8 (0.2 - 50 bar): SV 14 8-0,27 MS

-25°C to +180°C

Media:

Compressed air and other non-toxic non-inflammable gases, blown-off freely

Note:

These valves have been type approved and can only be supplied non-adjustable.

Optional:

Material 1.4404 (economical stainless steel) - ES2A, NPT thread NPT, fixed set pressure between 0.2 and 50 bar, TÜV adjustment certificate

*at 0° C / 760 torr

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.