

SV 38 8-8 MS



TÜV-säkerhetsventil G 3/8" (DN8), 8 bar, Mässing

Betyg: Inte betygsatt ännu

Pris

Pris 495,23 kr

Pris utan moms 396,18 kr

Rabatt

Momsbelopp 99,05 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Properties

Material Brass

Thread G 3/8"

reaction pressure [bar] 8.00

Blow-off capacity* [m³/h] 213

H [mm] 63

h [mm] 12

SW [mm] 20

Component identification markings TÜV.SV...882.8.DIG.0.65 CE0036 8 bar

Item description

Materials:

Body: brass, 1.4571 or 1.4401, seal: FKM

TÜV säkerhetsventil-fast, DN 8 (0.2 - 50 bar): SV 38 8-8 MS

Temperature range:

-25°C to +180°C

Media:

Compressed air and other non-toxic non-inflammable gases, blown-off freely

Note:

These valves have been type approved and can only be supplied non-adjustable.

Optional:

NPT thread -NPT, fixed pressure between 0.2 and 50 bar, TÜV adjustment certificate

*at 0° C / 760 torr

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.